

Specification Sheet

Adonis Stadium Floodlight Family Datasheet





Our Adonis Sports Light is specifically engineered for elevated installations in vast areas like outdoor sports fields, arenas and exhibition centres. With wattage options ranging from 600W to 1200W, this luminaire features a small beam angle, enabling precise targeting of specific zones while minimizing glare and ensuring uniform illumination. The module can be easily adjusted both vertically and horizontally to achieve optimal light distribution throughout the area.

Product Code	Wattage	Lumens	Dimensions	Weigl	ht EPA	Driver
SLLASFL/600 SLLASFL/800 SLLASFL/1000 SLLASFL/1200	600 800 1000 1200	96,000 128,000 160,000 192,000	685x595x410mm 685x595x410mm 695x675x410mm 695x675x410mm	27kg 27kg 32kg 32kg	0.298m²/3.2ft² 0.298m²/3.2ft² 0.392m²/4.22ft² 0.392m²/4.22ft²	UPOWERTEK UPOWERTEK INVENTRONICS INVENTRONICS
LED Type:			LED 5050			

Product:	Adonis Floodlight	LED Type:
Guarantee:	5 years	UGR level:
Lumen Output:	96,000 - 192,000	Surge Protection:
Lumens Per Watt:	160	Fixture Colour:
IP Rating:	IP66	Mounting Options:
IK Rating:	IK08	Material:
CRI:	>Ra70 (Ra80 optional)	Finish:
Driver Type:	Constant Current (CC)	Life Time of LED @Ta=
Power Factor:	>0.9	Life Time of LED @Ta=
Driver Type:	MOSO / Tridonic	Life Time of LED @Ta
Colour Temperature:	5000K (4000K, 5700K optional)	
Control:	Dimmable, DALI, DMX, Zigbee Wireless Control	
Input Voltage:	220-240VAC, 50-60 Hz	

LED Type:	LED 5050
UGR level:	NA
Surge Protection:	>10kV line-line, 20kV line-earth
Fixture Colour:	Black
Mounting Options:	Bracket Mounting
Material:	Aluminum Alloy, Glass and Polycarbonate Optical Le
Finish:	Powder Coating
Life Time of LED @Ta=25°C:	178,000 hrs-L70 B50
Life Time of LED @Ta=25°C:	111,000 hrs-L80 B50
Life Time of LED @Ta=25°C:	53,000 hrs-L90 B50






Operating Temperature:

Beam Angles:



-30°C to +40°C



LIFE. ILLUMINATED

Call today on 0151 420 6000 email sales@signatureledlighting.co.uk

Accessories	Codes
Optic Lens	SLLASFL/OL
DALI to 0-10V Converter	SLLASFL/DDC
Precision aiming device	SLLASFL/PAD
Safety rope	SLLASFL/SR

VISORS

Visor for up or down light (IES code: L80-B)	/VL80-B
Visor for up light control (IES code: L36)	/VL36
Visor for up light + side light control (IES code: L90)	/VL90
Visor for up light + side light control (IFS code: 196)	/VI 96

For more products visit www.signatureledlighting.co.uk