

Charity Wallpack Family Datasheet



Product Code	Wattage	Lumens	Dimensions	Unit Weight kg	Driver	Surge Protection
SLLCWP/10	10w	1550	196 x 96 x 186mm	1.42±0.2kg	UPSHINE	1KV line-line, 2KV line-earth
SLLCWP/20	20w	3100	196 x 96 x 186mm	1.42±0.2kg	UPSHINE	1KV line-line, 2KV line-earth
SLLCWP/30	30w	4650	196 x 96 x 186mm	1.42±0.2kg	UPSHINE	1KV line-line, 2KV line-earth
SLLCWP/40	40w	5800	282 x 125 x 205mm	2.76±0.2kg	DONE	4KV line-line, 6KV line-earth
SLLCWP/70	70w	10150	282 x 125 x 205mm	2.76±0.2kg	DONE	4KV line-line, 6KV line-earth

Our Charity LED Slim Wall Pack light is a sleek, low-profile lighting solution that offers exceptional performance, longevity, and low-maintenance operation. With a lightweight design, this wall pack light is a breeze to install and delivers outstanding results. It is the perfect replacement for traditional Slim Wall Pack light fixtures, providing an easy upgrade for your space.

Available in both silver and black models, this LED Slim Wall Pack light is designed to meet your aesthetic preferences while delivering high-quality lighting performance. Choose the Signatures Charity LED Slim Wall Pack light for a reliable, stylish lighting solution that exceeds your expectations

Specification

Product :	Charity Wall Pack	LED Type:	LED 3030
Guarantee:	5 years	Finish:	Silver or Black, Powder Coated
Lumen Output:	1550 - 10,150	Power Factor:	>0.95
Lumens Per Watt:	145 - 155	Diffuser Type:	Polystyrene - TPb rated *TPa available as a special
IP Rating:	IP66	Mounting Options:	Post Top, Side Entry
IK Rating:	IK08	Material:	Cast Aluminum, Polycarbonate Optical Lens
CRI:	>Ra70	Mounting Options:	Junction boxes or Surface mounting
UGR:	NA	Life Time of LED @Ta=25°C:	167,000 hrs-L70 B50
Inrush Current:	<60A	Life Time of LED @Ta=25°C:	100,000 hrs-L80 B50
Driver Type:	Constant Current (CC)	Life Time of LED @Ta=25°C:	45,000 hrs-L90 B50
Colour Temperature:	5000K (3000K,4000K optional)	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>10w/20w/30w</p> </div> <div style="text-align: center;"> <p>40w/70w</p> </div> </div>	
Voltage Range:	220-240Vac , 50 / 60 Hz		
Driver Type:	Constant Current (CC)		
Operating Temperature:	-30°C to +45°C		
Beam Angles:	10 - 30w U04201 40 - 70w R08401		

LIFE . ILLUMINATED

Call today on **0151 420 6000**
email sales@signatureledlighting.co.uk

For more products visit www.signatureledlighting.co.uk