

Specification Sheet

15W Plutus LED Half Moon or Full Moon Bulkhead

Our 15W Plutus Bulkhead is the ultimate in versatility, allowing for both ceiling and wall mounting, as well as indoor or outdoor use thanks to its IP66 rating.

The polycarbonate fitting is available in Black and White models and our customers can choose between a full moon or half-moon option. With an output of 1500 lumens the bulkhead is clearly illuminated, while keeping the LED chips hidden for a crisp, clean look.

Half-moon covers are water and dust resistant and by using our eyelid covers, installers have directional control of the distribution of light.



Available with Black or White finishes. Half Moon and Full Moon versions available.

Specification

| Product: | 15W Plutus Half Moon & Full Moon Bulkhead |
|---------------|--|
| Lumens: | 1500lm |
| CRI: | > 80 |
| Warranty: | 5 Years |
| IP Rating: | IP66 |
| IK Rating: | IK10 |
| Voltage: | 180 – 240V 50/60Hz |
| Power Factor: | PF: >0.85 |
| Lamp Size: | 300x95mm |
| Material: | Polycarbonate |

| Product | Code |
|-------------------------------------|---------------------|
| Standard Black Full Moon | SLL15WFM/CCT/B |
| Standard White Full Moon | SLL15WFM/CCT/W |
| Microwave Black Full Moon | SLL15WFM/CCT/MS/B |
| Microwave White Full Moon | SLL15WFM/CCT/MS/W |
| Emergency Black Full Moon | SLL15WFM/CCT/E/B |
| Emergency White Full Moon | SLL15WFM/CCT/E/W |
| Emergency Microwave Black Full Moon | SLL15WFM/CCT/E/MS/B |
| Emergency Microwave White Full Moon | SLL15WFM/CCT/E/MS/W |
| Corridor Function | SLL15WFM/CCT/MCF/ |
| Emergency Corridor Function | SLL15WFM/CCT/E/MCF/ |

LIFE. ILLUMINATED