

4ft Dual Colour Quad Wattage Trinity Pro

Our Trinity Pro is a flexible and slim luminaire with IP44 for multiple indoor applications such as educational buildings, healthcare, garages, offices, kitchens, and industrial buildings. It is suitable for surface-mounted or wall-mounted, rails bracket mounting, horizontal wires, and wire suspension.



Specification

Product :	SLL4FTTP/QW/CCT	Protective Class:	Class I
Wattage Power Adjustable:	23/29/35/40W	Profile:	White coating metal+PMMA prismatic diffuser
Guarantee:	5 years	Power Factor:	>0.9
Lumen Output:	3220/4060/4900/5600	Net Weight:	3.3Kg
Lumens Per Watt:	140	Mounting Options:	Surface mounted / Cable wire / Wire suspension/ Wall
IP Rating:	IP44	Service Life:	L80B10:100000h
IK Rating:	IK07	Photo-biological safety:	RG0
CRI:	80-95	Flicker factor:	<1%
UGR:	22	Wiring:	3/5 wires; 3/5 wires through
Beam Angle:	105°	Cable Entry:	One cable entry at each end cap and two top entries at the back of the luminaire
Colour Temperature:	3000K-4000K & 6000K	Product	
Supply Frequency:	50/60 Hz	SLL4FTTP/QW/CCT	
Input Supply Voltage:	AC 220~240V ; DC 180-264V	4ft Twin Trinity Pro Linear Fitting	
Operating Temperature:	-20°C - 40°C		
Overall Dimensions:	1195x155x52mm		

L I F E . I L L U M I N A T E D

Call today on 0151 420 6000

email sales@signatureledlighting.co.uk

For more products visit www.signatureledlighting.co.uk