

Typhon Post Top Light Family Datasheet

Our Typhon is a light weight compact post top light, three wattages well satisfy different applications. The special optics design contributes to comfortable visual experience.



Specification

Product Code	Wattage	Lumens
SLLTPSL/30	30w	3600
SLLTPSL/40	40w	4800
SLLTPSL/60	60w	7200

Product:	Typhon Post Top Light
Wattages:	30w / 40w / 60w
Guarantee:	5 years
Lumen Output:	3,600 - 7,200
Lumens Per Watt:	120
IP Rating:	IP66
IK Rating:	IK08
CRI:	>70 (Ra80 optional)
Colour Temperature:	4000K(3000,5000K Optional)
Surge Protection:	6KV line-line, 10KV line-earth
Power Supply:	Moso
Voltage Range:	120-240 Vac, 50 / 60 Hz
LEDs:	SMD 2835
Operating Temperature:	-30°C to + 50°C
Beam Angle:	90° - 120°

Product Dimension:	318x143mm
Luminaire Net Weight:	3.3kg
Driver Type:	Constant Current (CC)
Power Factor:	>0.95
Mounting Options & EPA:	Post top mounting - 0.08m ²
Material & Finish:	Aluminum alloy, Polycarbonate optical lens
Control:	Dimmable, DALI, Photocell
Life Time of LED @Ta=25°C:	31,000hrs - L90
Life Time of LED @Ta=25°C:	64,000hrs - L80
Life Time of LED @Ta=25°C:	101,000hrs - L70

Key Features

- Three wattages, 30W, 40W, 60W.
- System efficiency up to 120lm/w, lumen package 3600lm-7200lm.
- Photocell optional.
- IP66 & IK08 double protection.
- Low UGR, visual comfortable.

Applications

- Village streets
- Urban road
- Country yard
- Parking lot
- Walk path
- Park

LIFE . ILLUMINATED

Call today on **0151 420 6000**

email sales@signatureledlighting.co.uk

For more products visit www.signatureledlighting.co.uk