

Uhtred LED Linear High Bay Light Family Datasheet


Our Uhtred LED linear high bay light is designed for distribution channel, simple and compact with high end quality, available in different wattages, from 100W-200W. Multiple lighting distribution optional, Including a variety of angle design, which will be a great help in different applications.



Product Code	Wattage	Lumens	Weight
SLULHB/100	100w	16000	4.6±0.3kg
SLULHB/150	150w	24000	4.9 ± 0.3kg
SLULHB/200	200w	32000	5.3 + 0.3kg

Specification

Product:	Uhtred LED Linear High Bay	Product Dimension:	600×281×59mm
Family Wattages:	100 / 150/ 200w	Luminaire Net Weight:	100w 4.6±0.3kg - 150w 4.9±0.3kg - 200w 5.0±0.3kg
Guarantee:	5 years	Driver Type:	Constant Current (CC)
Lumen Output:	16,000 - 32,000lm	Power Factor:	>0.90
Lumens Per Watt:	160	Mounting Options:	Suspension Mounting
IP Rating:	IP20	Material & Finish:	Aluminum alloy, PMMA Lens, Sandblasting oxidation
IK Rating:	IK04	Control:	1-10V / DALI Dimmable
CRI:	>70 (Ra80 optional)	Life Time of LED @Ta=25°C:	54,000hrs - L90
Colour Temperature:	5000K - 4000K Optional	Life Time of LED @Ta=25°C:	114,000hrs - L80
Surge Protection:	6KV line-line, 10KV line-earth	Life Time of LED @Ta=25°C:	182,000 hrs - L70
Power Supply:	Sonsen		
Voltage Range:	220-240 Vac, 50 / 60 Hz		
LEDs:	SMD 2835		
Operating Temperature:	-30°C to +45°C		
Beam Angles:	40°100°, 60°90°, 70°100°, 110°100°, 90°100°		



Key Features

- Integrated design 100w to 200w.
- Efficiency up to 160lm/W
- DALI, 1-10V Dimming optional
- Fast installation and easy maintenance.
- Aluminum alloy lamp body with sandblasting anodize treatment offer strong anti-corrosion ability.

LIFE . ILLUMINATED

Call today on 0151 420 6000

email sales@signatureledlighting.co.uk

For more products visit www.signatureledlighting.co.uk